

TETRA-CHEM INDUSTRIES LTD.

271 INGERSOLL ST. S. INGERSOLL, ONTARIO CANADA N5C 3J7

TEL: (519) 485-4370 TOLL FREE: (888) 658-5515 FAX: (855) 762-4446 EMAIL: info@tetra-chem.com WEB SITE: www.tetra-chem.com

SPECIALTY CHEMISTRY

WASTE MANAGEMENT

APPLICATION TECHNOLOGY

INNOVATIVE ENGINEERING

Product Application Presentation

Product Identifier:

TCI 119 H.D.

Process Identifier: Ultra-Purity Non-Residual Orange Extract "Adhesive & Glue" Cleaning Solvent

Product Presentation

TCI 119 H.D. biodegradable solvent vinyl graphics glue & adhesive stripper is a neutral, concentrated, high flash point, non-corrosive amber liquid formulation incorporating several natural complex hydrocarbon solvents for solubilizing almost all types of glues and adhesives commonly used in the T-Shirt Imprinting industry on all types of composite, laminate, metal and painted surfaces. It quickly penetrates the organic or aqueous compound structure and breaks it up into emulsifiable particles for easy wiping.

Process Introduction

TCI 119 H.D. is applied with a low pressure spray system using a pressurized tank sprayer i.e. sure-shot mechanism. In the graphics industry it is suitable for the removal of all types of residual glues and adhesives. Spray on, soak for a minute scrape and wipe off. In the T-Shirt Imprinting industry the overspray of spray mist adhesive on process equipment and the floor can be presoaked and removed easily using a cold water power washer.

TCI 119 H.D. will not affect metal or painted surfaces during exposure.

Process Specificity

Important Notice

Apply **TCI 119 H.D.** before introducing water to the glue or adhesive.

Spray and thoroughly soak the area to be cleaned. Allow 1–20 minutes for penetration depending on the type of glue and adhesive thickness. Agitate with a stiff brush to dissolve the soil matrix. Rinse with water via a damp cloth, hot or cold water power washer. Area cleaned with TCI 119 H.D. will be film free for further operations. Pretest on painted surfaces before using.

Packaging: 20, 205 litres and siphon pump

For industrial and institutional use only.