



TETRA-CHEM
INDUSTRIES LTD.

271 INGERSOLL ST. S.
INGERSOLL, ONTARIO
CANADA N5C 3J7

TEL: (519) 485-4370
TOLL FREE: (888) 658-5515
FAX: (855) 762-4446
EMAIL: info@tetra-chem.com
WEB SITE: www.tetra-chem.com

SPECIALTY CHEMISTRY

WASTE MANAGEMENT

APPLICATION TECHNOLOGY

INNOVATIVE ENGINEERING

Product Application Presentation

Product Identifier:

TCI 301-50 H.D.

Process Identifier: Inhibited hydrochloric acid cement, lime, scale, concrete and rust remover (15%)

Product Introduction

TCI 301-50 H.D. is a ready to use complex liquid formulation of environmentally friendly acids with unique fume suppressants and stable biodegradable wetting agents.

TCI 301-50 H.D. is inhibited against metal substrate corrosion by 99.9%.

Process Introduction

TCI 301-50 H.D. formula effectively removes light-heavy deposits of residual cement, efflorescence from masonry, concrete, mortar, rust, scale, lime, drywall compound, most salt compounds except Barium Sulphate, stucco and plaster with minimal time and effort. It is designed for the construction industry to clean equipment used in hauling cement, on-site process mixers, ready-mix trucks and chutes. It is used for the clean-up of splatter, tools, forms, wheelbarrows etc.

Precautionary Notes

Do not let any chemical solution dry on any surface (concentrates may cause irreversible damage), be careful to protect people, plants and animals, stationary and mobile property from wind drift.

Accessories on finished products, such as light assemblies, reflectors, glass & mirrors, plastics, brass, stainless steel, hard chrome, decals, logos, wood, tarps, mud flaps or rubber tires are not altered or defaced by this chemical solution when used according to directions.

Application Procedure

This procedure is for trained personnel only.

Small tools manual cleaning method: For cleaning of small tools in the maintenance shop or off-site use a plastic pail or tray and brush. Pour the remaining liquid back into the original shipping container.

Large tools and equipment cleaning method: To start the cleaning process, set up the manufacturer's approved chemical applicator system and regulate the operating air pressure to 340-400 kPa (50-60 psi). The system draws the cleaner directly from the shipping container and delivers it through a variable length discharge hose directly to the dirty equipment without the cleaning crew having to handle or come in close proximity with the hazardous product. The pump will start and stop automatically by controlling the flow on demand at the shut-off valve on the applicator wand.

Caution: Do not spray TCI 301-50 H.D. directly onto a hot surface since it will result in stains or damage.

Use a pressure washer and walk around the whole unit being treated and thoroughly cool and wet the entire surface on a hot sunny day or any other time. The best time is early in the morning or evenings or in a controlled environment. Now apply the chemical solution as a spray to the entire body starting from the top and working down. Assure complete thin film coverage. Once the application

is complete, re-apply the product to the remaining heavy encrustations and allow approximately a 5 minute chemical exposure time. Exposure time is directly proportional to soil thickness. Brushing is optional.

Rinse the entire body with high pressure (2500-3000 psi) cold water starting at the bottom and consistently moving with a 6 inch fan or less in a horizontal pattern until the top is reached. Then rinse all residual chemical solution thoroughly from the top down. It is recommended to use the down stream chemical injection device on the power washer (TCI 710 H.D.) to neutralize excess acid on the equipment and to control the pH of ground contamination, storm and sanitary sewer systems. This cleaning process does not generate a hazardous waste.

Caution: Do not let any chemical dry on the surface (wind drift chemical spray is a potential danger). Concentrated chemical without water may stain surfaces if not rinsed.

Packaging: 20, 205, 1000 litres

For industrial and institutional use only.

The information given herein is given in good faith but no warranty, expressed or implied is made.

Please call our technical support line at 1-888-658-5515 for solutions to your industry.

Copyright 2016 Tetra-Chem Industries Ltd. All rights reserved. Printed in Canada.

No part of this publication may be reproduced or distributed in any form or by any means, or stored in a database or retrieval system, without the prior written permission of the publisher.

