



TETRA-CHEM INDUSTRIES LTD.

271 INGERSOLL ST. S.
INGERSOLL, ONTARIO
CANADA N5C 3J7

TEL: (519) 485-4370
TOLL FREE: (888) 658-5515
FAX: (855) 762-4446
EMAIL: info@tetra-chem.com
WEB SITE: www.tetra-chem.com

SPECIALTY CHEMISTRY

WASTE MANAGEMENT

APPLICATION TECHNOLOGY

INNOVATIVE ENGINEERING

Product Application Presentation

Product Identifier:

TCI 3300-60 H.D. (-55°C)

Process Identifier:

All-season global long life engine coolant/antifreeze 60/40 heat transfer fluid

Product Presentation

TCI 3300-60 H.D. is a **READY TO USE** low viscosity **RED** liquid. It is a blend of mono and di ethylene glycol and Chloride free deionized water. This features a water/glycol freeze point depression to -55°C and boil over point at 135°C.

A dual synergistic inhibitor package of Organic Acid Technology is responsible for the corrosion protection developed for this coolant. OAT's are Long Life Coolants (LLC), based on minimally depleting Carboxylate Technology. This technology provides superior protection to all components of the cooling system including brass, copper, aluminum and magnesium found in the modern day engines heat sink circulation system.

Unlike the past traditional coolant packages containing AMINES, BORATES, NITRITES AND SILICATES and the need for regular additions of Supplemental Coolant Additives (SCA's) at scheduled service intervals is thus no longer required, providing a true Long Life product. In some heavy duty diesel applications you may see a reference to a Coolant Extender. A Coolant Extender can be used with an OAT coolant to top-up certain additives at the products half life which is typically around 480,000 kms. In general OAT based corrosion inhibitors are recognized for their non-toxic properties making them readily biodegradable in compliance with any environmental and occupational health & safety obligations.

CAUTION - POISON

SWEET ODOUR & TASTE

KEEP OUT OF REACH OF CHILDREN AND PETS

Process Introduction

TCI 3300-60 H.D. is designed for use in the recirculating cooling system of all kinds of global motorized equipment and transportation vehicles to maintain efficient engine temperature.

TCI 3300-60 H.D. has excellent thermal conductivity, high specific heat and low viscosity. It maintains good thermal distribution between the different mechanical parts and metal compositions so as to restrict thermal expansion and retain operating clearances.

TCI 3300-60 H.D. prevents sludge formation in the cooling system's water galleries which can impede the heat transfer efficiency over time resulting in costly engine and radiator failure.



110 VAC or 12 VDC DEMAND PUMP
BULK DISPENSING SYSTEM @ 5gpm

Process Specificity

This prescribed **READY-TO-USE** formulation **TCI 3300-60 H.D.** is a functional engine coolant that meets the following performance requirements for:

ASTM D3306, D4985, D6210, D7583

JIS K2234

AS/NZS 2108.1:1997 "Type A"

Kenworth R026-170-97

BS 6580, BS5117

MACK 014GS17004

Caterpillar EC-1

MAN 324

CID-A-A-52624

MTU MTL 5048

Cummins 3666132, 14603

PACCAR CS0185

Detroit Diesel 7SE 298, 93K217

Peterbilt 8502.002

Freightliner 48-22880

TMC RP 338

GM 1825M, 1899M and Heavy Truck

TMC RP 329B

Navistar/ ITE CEMS B-1

Volvo

CONTACT SUPPLIER FOR
ADDITIONAL SAFE PRODUCT
APPLICATION PROCEDURES

TCI 3300-50 H.D. PROVIDES
FREEZE PROTECTION TO -37°C

For industrial and institutional use only.

The information given herein is given in good faith but no warranty, expressed or implied is made.

Please call our technical support line at 1-888-658-5515 for solutions to your industry.

Copyright 2016 Tetra-Chem Industries Ltd. All rights reserved. Printed in Canada.

No part of this publication may be reproduced or distributed in any form or by any means, or stored in a database or retrieval system, without the prior written permission of the publisher.