# Safety Data Sheet

# Section 1: Product identification and use

# **Product Identifier:** Process Identifier:

**TCI 1218 H.D.** Foaming Livestock Barn pre-soak (30-60min) Dilute at 1-2% (10-20ml per 1 L)

Supplier's name and address:

P260-Do not breathe mist or spray.

fresh air and keep comfortable for breathing.

application to the affected areas (see SDS).

international regulations as specified.

P405-Store locked up.

P363-Wash contaminated clothing before reuse.

P390—Absorb spillage to prevent material damage.

P406-Store in a corrosive resistant HDPE container.

lenses, if present and easy to do so. Continue rinsing. P310-Go to the hospital emergency immediately take SDS.

P264-Wash hands and/or gloves thoroughly after handling.

skin with plenty of water or use shower if available for 30 minutes.

P337+P313-If eye irritation persists get medical advice/attention.

Tetra-Chem Industries Ltd.

271 Ingersoll St. S., Ingersoll ON N5C 3J7 Canada

Phone: 519-485-4370 - Toll free: 888-658-5515

P303+P361+P353-IF ON SKIN (or hair): Remove all contaminated clothing immediately. Rinse

P304+P340-IF INHALED: Go to the hospital emergency immediately take SDS. Remove person to

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

P321-Specific treatment First Aid: Always have a 5% Vinegar solution on hand for immediate

P501-Dispose of contents/container per SECTION 12 in accordance with local/regional/national/

P280-Wear protective gloves, protective clothing, eye protection and face protection.

P301+P312-IF SWALLOWED: Go to the hospital emergency immediately take SDS. P301+P330+P331-IF SWALLOWED: Rinse mouth with water. Do not induce vomiting.

24H EMERGENCY: 613-996-6666

#### Manufacturer's name and address:

# Tetra-Chem Industries Ltd.

271 Ingersoll St. S., Ingersoll ON N5C 3J7 Canada Phone: 519-485-4370 - Toll free: 888-658-5515

#### Section 2: Hazard identification

GHS Classification Corrosive To Metals: Category 1 Skin Corrosion: Category 1A Eye Irritation: Category 2A



DANGER Hazard Statements H290-May be corrosive to metal. H302-Harmful if swallowed H314—Causes severe skin burns and eye damage. H319-Causes serious eye irritation. **Precautionary Statements** P234-Keep only in original container.

#### Section 3: Composition / information on ingredients

Section 3. Composition / Information on ingredients			
Hazardous Ingredients:	CHEMICAL NAME Potassium Hydroxide	CAS NUMBER 1310-58-3	CONCENTRATION [%] 10 - 30
Section 4: First aid measures			
Description of First Aid Measures General: Determine areas of exposure. Inhalation: Excessive exposure - move the fresh air. Skin Contact: Wash with cold water or neutralize with 5% vinegar solution. Eye Contact: Remove contact lenses. Rinse with cold water or saline solution. Ingestion: If victim is conscious administer 5% vinegar solution. Seek immediate medical attention. Do not induce vomiting.		Most Important Symptoms and Effects Both Acute and Delayed General: Low risk to adverse health effects. Inhalation: Respiratory irritation or sore throat. Skin Contact: Severe skin burns. Eye Contact: The alkali solution can travel to the back of the eye ball and corrode the optic nerr if sprayed directly into the eyes. The delayed effect symptoms are a scaly rash for 3-4 days whe blinking. Seek medical attention. Ingestion: Burning sensation just like acid reflux. Seek medical attention.	
Section 5: Fire-fighting measu	ires		
Extinguishing Media Suitable Extinguishing Media: Evaluate based on surrounding fire. Unsuitable Extinguishing Media: Evaluate based on surrounding fire. Special Hazards Arising From the Substance or Mixture Fire Hazard: Corrosive caustic vapours at high temperatures.		Reactivity: No risk. Advice for Firefighters Precautionary Measures Fire: Evaluate based on surrounding fire. Firefighting Instructions: Evaluate based on surrounding fire. Protection During Firefighting: Evaluate based on surrounding fire.	

Explosion Hazard: No risk.

#### Section 6: Accidental release measures

Personal Precautions, Protective Equipment and Emergency Procedures General Measures: Wear impervious splash protection. Neutralize with copious amounts of	For Emergency Personnel Protective Equipment: Wear impervious splash protection.	
water or safe acid solutions and flush to sanitary sewers if at pH 8.5.	Emergency Procedures: Neutralize with copious amounts of water or safe acid solutions and	
For Non-Emergency Personnel	flush to sanitary sewers if the pH is below 8.5 and above 5.5.	
Protective Equipment: Wear impervious splash protection.		
Emergency Procedures: Mop up small spills with water and flush to sanitary sewers. Large spills	Environmental Precautions	
should be contained and reported immediately.	Methods and Material for Containment and Cleaning Up	
Phone Number of your local authority for Emergency Spill Response:	For Containment: Water/oil absorbent pads.	
	Methods for Cleaning Up: Mop up small spills and dispose to sanitary sewer.	

#### Section 7: Handling and storage

Precautions for Safe Handling

Additional Hazards When Processed: Use only Manufacturer supplied storage and/or dispensing equipment. See GHS WORKPLACE LABEL in your work area. Hygiene Measures: Do not eat, drink or smoke while using this product. Personal Protection Equipment required for cleaning process. Storage Conditions: Keep only in original containers. Incompatible Materials: Do not mix with other cleaners.

Special Rules on Packaging: Consult Manufacturer or Supplier.

Hazardous Combustion Products: Oxides of Carbon, Caustic vapours,

Specific End Use(s) TCI 1218 H.D. Foaming Livestock Barn pre-soak (30-60min) Dilute at 1-2% (10-20ml per 1 L) is used to remove complex residues from food service establishments kitchen fume hoods, walls, floors. Scan Label QR for Product Application Sheet and SDS for safe intended use.

# Section 8: Exposure controls / personal protection

Section 9: Physical and chemical properties

### **Control Parameters**

ACGIH TLV: 15 mg/m<sup>3</sup> (TWA) 175 ppm (SKIN 500 mg/m<sup>3</sup> (INHALATION) OSHA PEL: 15 mg/m<sup>3</sup> (TWA) 175 ppm (SKIN) 500 mg/m<sup>3</sup> (INHALATION)

# Exposure Controls

Appropriate Engineering Controls: Adequate ventilation to meet exposure limits by removing the hazard from an inside or outside work environment. The chemical constituents of the cleaning solution does not evaporate.





**Other Information:** Alkali resistant GLOVES are always required. In confined wash areas with minimal ventilation use NIOSH approved respirators and splash protection for alkaline mist when rinsing parts.

Section 5. Physical and chemical properties	
Information on Basic Physical and Chemical Properties Physical State: Liquid. Appearance: Water clear with slight tint of amber. Odour: Detergent. Odour Threshold: Not available. pH: 13 Relative Evaporation Rate (butyl acetate=1): 0.3 Melting Point: Not applicable. Freezing Point: 0°C Boiling Point: 100°C. Flash Point: Not applicable. Auto-ignition Temperature: Not applicable.	Decomposition Temperature: Not applicable. Flammability (solid/gas): Not applicable. Lower Flammable Limit: Not applicable. Upper Flammable Limit: Not applicable. Vapour Pressure: Not applicable. Relative Vapour Density at 20°C: Not applicable Relative Density (water=1): 1.03 Solubility in Water: Complete Partition coefficient: n-octanol/water: Not applicable. Viscosity: 20 centipoise @ 20°C. Explosion Data - Sensitivity to Mechanical Impact: Not applicable. Explosion Data - Sensitivity to Static Discharge: Not applicable.
Section 10: Stability and reactivity	
Reactivity: Reacts violently with strong acids. Chemical Stability: Stable. Possibility of Hazardous Reactions: None when used as directed. Conditions to Avoid: Strong oxidizers.	Incompatible Materials: White metals or their alloys: aluminum, magnesium, lead, tin, zinc, brass and babbitt. Hazardous Decomposition Products: Hydrogen release from above metals.
Section 11: Toxicological information	
Information on Toxicological Effects - Product Acute Toxicity: Not available. LD <sub>50</sub> Data (Species-Route): 273 mg/kg(Rat - oral). LC <sub>50</sub> Data (Species-Route): Not available. Skin Corrosion/Irritation: Severe irritant: Human/Rabbit 50 mg/24hrs Serious Eye Damage/Irritation: Moderate corneal injury: Rabbit 1 mg/24hrs Respiratory or Skin Sensitization: Not suspected. Germ Cell Mutagenicity: Not suspected. Teratogenicity: Not suspected. Carcinogenicity: Not suspected.	Specific Target Organ Toxicity (Repeated Exposure): Not available. Reproductive Toxicity: Not suspected. Specific Target Organ Toxicity (Single Exposure): Not suspected. Aspiration Hazard: Not anticipated. Symptoms/Injuries After Inhalation: Irritation/burning sensation. Symptoms/Injuries After Skin Contact: Slight irritation/redness observation. Symptoms/Injuries After Eye Contact: Stinging/scaly sensation. Tearing/Redness. Symptoms/Injuries After Ingestion: Sore throat/burns. Information on Toxicological Effects - Ingredients Large doses can change the body's pH and electrolyte balance.
Section 12: Ecological information	
<b>Toxicity:</b> Not applicable when used as directed. <b>Mobility in Soil:</b> Neutralizes and turns to salt in soil. Detergents are biodegradable.	Other Adverse Effects Other Information: No unusual adverse effects encountered.

#### Section 13: Disposal considerations

Waste Disposal Recommendations: Consult Manufacturer or Supplier. Additional Information: The cleaning process may generate a hazardous industrial waste. Comply with Canadian Ministry of Environment and Climate Change: Regulation 347 and local municipal by-laws. Comply with US EPA's federal, state & local

# Section 14: Transport information

TDGA CANADA - DANGEROUS GOODS: REGULATED 49 CFR (USA) DANGEROUS GOODS: REGULATED IMDG (VESSEL) DANGEROUS GOODS: REGULATED IATA (CARGO AIR) DANGEROUS GOODS: REGULATED IMDG (PASSENGER AIR) DANGEROUS GOODS: REGULATED regulations. Tetra-Chem Industries Ltd. is licensed by the Ministry of the Environment and Climate Change for waste management. Ontario Certificate of Approval # A 800506.

Provincial Waste Class: Waste stream to be determined for treatment method.

EMERGENCY ASSISTANCE: CANADA Canutec 1-888-CANUTEC (1-888-226-8832)



Proper Shipping Name: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. Hazard Class: 8 Identification Number: UN3266 Packing Group: III Label/Placard Codes: 8

#### Section 15: Regulatory information

CANADA: All ingredients are listed on the DSL Domestic Substance List.

USA: All ingredients are listed on the TSCA Toxic Substances Control Act.

Section 16: Other information

Prepared by: Health and Safety committee Contact: A. Struthmann (Hon. BSc.) Telephone: 1-519-536-1617 Date prepared: 2024-01-29

Additional information: The information in this SDS has been obtained from sources believed to be reliable. The manufacturer and supplier provides no warranties express or implied and assumes no responsibility for the accuracy or the completeness of the data contained herein.